



# C 9 SUR II

## SURROUNDS

### 50 YEAR LEGACY

For more than half a century, Jamo has designed and engineered high-performance audio products to integrate beautifully into any environment. Our innovative loudspeakers are ideal for the spaces where you live and play, and will provide enjoyment for years to come.

### A MODERN CLASSIC

The Concert Series has long served as the flagship line of the historic Jamo Speaker brand. The new Concert 9 Series II perfectly melds premium acoustic performance with a modern, luxurious design to create gorgeous furniture whose exceptional acoustics are surpassed only by their beauty. High quality wood grain finishes, full length woven tweed grilles, satin painted MDF baffles, all new sleeker chrome logos, satin aluminum trim rings, centre plugs and stabilizer feet make the Concert 9 series II aesthetically elegant, while providing exceptional acoustic performance.

### SUPERIOR ACOUSTIC TECHNOLOGY

The C 9 SUR II is an 3-way sealed surround speaker, designed for exceptional detail and balanced, dynamic reproduction of surround effects. Patented Midrange Phase Diffusion technology ensures phase correlation with the front stage for lifelike, powerful surround effects that combine perfectly with the other speakers in your system. Hybrid Composition Conical Cone (HCCC) woofer and midrange provide the stiffness and strength of aluminum or titanium, with the transient response and smoothness of wood fibre, while with Long Displacement Surround (LDS) for cleaner, tighter, and deeper bass. Paired with the 1" Silk dome tweeter mated to an Anti-Diffraction Waveguide for exceptionally smooth high frequency extension and detail, both on-axis and off, the Jamo Concert C 9 SUR II surround speaker is custom tuned to bring your surround sound experience to life.

### SPECIFICATIONS

SYSTEM TYPE	3-Way Sealed
FREQUENCY RESPONSE +/- 3DB	80Hz - 24kHz
SENSITIVITY @ 2.83V / 1M	87 dB
HIGH FREQUENCY DRIVER (MM / IN)	25 / 1 Silk Dome with WaveGuide
MID RANGE DRIVERS (MM / IN)	95.3 / 3.75 HCCC Cone
LOW FREQUENCY DRIVER (MM / IN)	101.6 / 4 HCCC Cone
IMPEDANCE	6 Ohm
POWER HANDLING (CONT/PEAK)	120 / 240
INPUTS	Chrome plated screw terminals
DIMENSIONS (MM / IN, HXWXD)	350 X 318.5 X 196 / 13.8 x 12.5 x 7.7
WEIGHT (KG / LBS)	8.2 / 18
FINISHES	Black Ash, White Oak, Dark Apple

# Jamo®

## CONCERT 9 SERIES