NuQ NuQ118B-AN

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking



- 3,000 Watt power featuring KLARK TEKNIK Class-D technology
- KLARK TEKNIK Digital Signal Processing for total system control
- ULTRANET digital audio networking connects to mixers and other sources
- Double suspension 18" low frequency driver with inside/outside wound coil
- Fully featured user interface with LCD display for ease of navigation
- PC remote control software downloadable at turbosound.com
- Low distortion dual port design for maximum sound pressure level
- 18 mm (¾") birch plywood enclosure with hard wearing semi matt black paint finish
- Integral M10 rigging points for ease of installation
- 35 mm pole mount to support satellite speaker
- Mains input on Neutrik powerCON* connector
- 3-Year Warranty Program**
- Designed and engineered in England



The 3,000 Watt NuQ118B-AN is a powered 18" dual ported bandpass enclosure that is optimally tuned for extended low frequency response. Designed to work individually without a controller, the NuQ118B-AN provides very high output FOH performance and is ideally suited for a wide range of music and live sound reinforcement applications.



The NuQ118B-AN features a powerful, double suspension 18" low frequency driver that utilizes a specialised inside/outside wound voice coil for higher magnetic density, better heat dissipation, high power handling capacity, and improved efficiency. For its size and operating bandwidth, the NuQ118B-AN delivers extremely high output that is virtually distortion-free – even in the most demanding applications.

Output power for the NuQ118B-AN is provided by means of an efficient and lightweight KLARK TEKNIK 3,000-Watt Class-D power amplifier. A sophisticated, but easy to use KLARK TEKNIK Digital Signal Processor (DSP) provides dynamic EQ for impressive low frequency response at low volume levels and transparent limiting for clarity at high output levels – and for long-term reliability.

^{*}All third-party trademarks are the property of their respective owners. Their use neither constitutes a claim of the trademark nor affiliation of the trademark wowners with MUSIC Group. Product names are mentioned solely as a reference for companibility, effects and/or companents.

NuQ NuQ118B-AN

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking

On the rear panel of the amplifier module, the user interface's LCD display and single rotary encoder provide intuitive access to: position compensation, user EQ control, crossover alignment and signal routing features. In addition to the balanced XLR input, an XLR output is provided for daisy-chaining more active subwoofers, or for use with active full range satellite speakers. An onboard USB port provides access for remote control of the NuQ118B-AN via PC computer, as well as DSP firmware updates.


ULTRANET connectivity is provided by two locking etherCON* connectors. Up to 16 independent channels of 24-bit digital audio and control data are transmitted via a single CAT5 cable between compatible digital devices – including mixers, I/O stage boxes, powered loudspeakers and personal monitoring systems. Simplified cable routing and ease of setup translate directly into significant time saved during installation.

Finished in a highly durable semi matt black paint, the cabinet is constructed from 18 mm (¾") birch plywood and includes: multiple M10 threaded rigging points; a 35 mm pole socket for satellite speaker mounting; integrated carry handles for convenient transport – and high impact interlocking corners for ground stacking stability. Mains power input is provided via a Neutrik powerCON* connector.

NuQ NuQ118B-AN


3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking


Frequency Response Sensitivity 1 W / 1 m



3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking

Dimensions





NuQ NuQ118B-AN

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking

Technical Specifications

System	
Frequency Response	40 Hz – 150 Hz ±3 dB
rrequency nesponse	33 Hz – 150 Hz -10 dB
-	
Nominal Dispersion	Half Space
Maximum SPL	136 dB peak
Crossover type	Active
Transducers	1 x 18" (460 mm) LF driver
Limiter	Peak and rms

Amplifier		
Maximum Output Power*	3000W	
Туре	Class-D	
Protection	Short circuit, thermal	

1 x Combo Jack/XLR 1 x XLR
+4dBu or +14 dBu software switchable
40 kΩ balanced
+22 dBu
2 x RJ45
Neutrik powerCON 20A†

Controls	
DSP	Rotary push-encoder and level control
	Buttons for Process, Setup, Exit, Enter

User DSP Functions	
Factory EQ Presets	Positioning, Sound mode
Display	LCD 128 x 32, blue, backlit
Delay	0 - 300 ms
Equalisation	High and low shelving EQ 2 x parametric EQ
Limiter	Zero attack input limiter
Presets	20 total presets, 19 user-definable
Crossover	Low Pass L-R 24 dB/oct
Protection	Lock-out function for all settings

Ultranet Digital Network	
Digital processing	
A/D conversion	24-bit,44.1/48kHz sample rate
Converter type	24-bit,delta-sigma
System	
Signal	16 channels
Latency	< 0.9 ms
Frequency response	20 Hz to 20 kHz (+0 / -3 dB)
Dynamic range	typical 92 dB
Cabling	
Cables	Shielded CAT5
Cable length	max. 246 ft / 75 m recommended

NuQ NuQ118B-AN

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking

Power Supply	
Power consumption	180W @ 1/8 max power
Voltage (fuses)	
USA / Canada	120 V~, 60 Hz (T 15 A H 250 V)
UK / Australia / Europe	220-240 V~, 50/60 Hz (T 10 A H 250 V)
Korea / China	220-240 V~, 50/60 Hz (T 10 A H 250 V)
Japan	100 V~, 50/60 Hz (T 15 A H 250 V)

Enclosure	
Dimensions HWD	773 x 579 x 700 mm (30.4 x 22.8 x 27.6")
Net weight	57.9 kg (127.5 lbs)
Construction	18 mm (¾") birch plywood
Finish	Semi matt black paint
Grille	Powder coated perforated steel
Flying hardware	M10 x 16 points

^{*}independent of limiters and driver protection circuits

 $\ \, \text{†Only qualified personnel are allowed to modify the AC-Main cord and to adhere to all applicable national standards}.$

 $^{{\}it †} Neutrik \ and \ power CON \ speak ON \ are \ registered \ trademarks \ of \ Neutrik \ AG.$

NuQ NuQ118B-AN

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking

Architecture & Engineering Specifications

The loudspeaker shall be of the powered subwoofer type, consisting of one 18" (460 mm) LF driver. Performance specifications of a typical production unit shall meet or exceed the following: frequency response, measured with swept sine wave input, shall be flat within ± 3 dB from 40 Hz to 150 Hz and within -10 dB from 33 Hz to 150 Hz. Nominal dispersion shall be "half space." Maximum amplifier output power shall be 3,000 Watts peak, independent of limiters and driver protection circuits. Maximum SPL (peak), measured at 1 metre with music program, shall be 13 (dB. Dimensions: 773 mm high x 579 mm wide x 700 mm deep (30.4" x 22.8" x 27.6"). Net weight: 57.9 kg (127.5 lbs). The loudspeaker system shall be the TURBOSOUND NuQ118B-AN. No other loudspeaker shall be acceptable unless submitted data from an independent test laboratory verifies that the above combined performance / size specifications are equaled or exceeded.

3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking



3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking



3000 Watt 18" Band Pass Subwoofer with KLARK TEKNIK DSP Technology and ULTRANET Networking







For service, support or more information contact the TURBOSOUND location nearest you:

Europe MUSIC Group Services UK Tel: +44 156 273 2290 Email: CARE@music-group.com

USA/Canada MUSIC Group Services NV Inc. Tel: +1 702 800 8290 Email: CARE@music-group.com Japan MUSIC Group Services JP K.K. Tel.: +813 6231 0454 Email: CARE@music-group.com