

AT4047/SV CARDIOID CONDENSER MICROPHONE

(4°) S E R I E S



- Transformer-coupled output and a specially tuned element provide warm sonic characteristics reminiscent of early F.E.T. studio microphone designs
- Exceptionally wide dynamic range, low self-noise and high SPL capability for maximum versatility
- Dual-diaphragm capsule design maintains precise cardioid pattern definition across the full frequency range of the microphone
- Precision-machined, nickel-plated brass, acoustic element baffle provides enhanced element stability and optimal sensitivity
- State-of-the-art surface-mount electronics ensure compliance with A-T's stringent consistency and reliability standards

The AT4047/SV is intended for use in professional applications where remote power is available. It requires 48V DC phantom power, which may be provided by a mixer or console, or by a separate, in-line source such as the Audio-Technica AT8801 single-channel and CP8506 four-channel phantom power supplies.

Output from the microphone's XLRM-type connector is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot" – positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

An integral 80 Hz high-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The high-pass position reduces the microphone's sensitivity to popping in close vocal use. It also reduces the pickup of low-frequency ambient noise (such as traffic, air-handling systems, etc.), room reverberation and mechanically coupled vibrations.

In use, secure the cable to the mic stand or boom, leaving a slack loop at the mic. This will ensure the most effective shock isolation and reduce the possibility of accidentally pulling the microphone out of its mount.

Avoid leaving the microphone in the open sun or in areas where temperatures exceed 110° F (43° C) for extended periods. Extremely high humidity should also be avoided.

AT4047/SV SPECIFICATIONS†


ELEMENT	Externally polarized (DC bias) condenser
POLAR PATTERN	Cardioid
FREQUENCY RESPONSE	20-18,000 Hz
LOW FREQUENCY ROLL-OFF	80 Hz, 12 dB/octave
OPEN CIRCUIT SENSITIVITY	-35 dB (17.7 mV) re 1V at 1 Pa*
IMPEDANCE	250 ohms
MAXIMUM INPUT SOUND LEVEL	149 dB SPL, 1 kHz at 1% T.H.D.; 159 dB SPL, with 10 dB pad (nominal)
NOISE†	9 dB SPL
DYNAMIC RANGE (typical)	140 dB, 1 kHz at Max SPL
SIGNAL-TO-NOISE RATIO†	85 dB, 1 kHz at 1 Pa*
PHANTOM POWER REQUIREMENTS	48V DC, 3.0 mA typical
SWITCHES	Flat, roll-off; 10 dB pad (nominal)
WEIGHT (less accessories)	14.5 oz (410 g)
DIMENSIONS	6.69" (170.0 mm) long, 2.10" (53.4 mm) maximum body diameter
OUTPUT CONNECTOR	Integral 3-pin XLRM-type
ACCESSORIES FURNISHED	AT8449/SV shock mount for 5/8"-27 threaded stands; microphone dust cover; protective carrying case

†In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.

*1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

† Typical, A-weighted, using Audio Precision System One.

Specifications are subject to change without notice.



One-Year Limited Warranty

Audio-Technica brand products purchased in the U.S.A. are warranted for one year from date of purchase by Audio-Technica U.S., Inc. (A.T.U.S.) to be free of defects in materials and workmanship. In event of such defect, product will be repaired promptly without charge or, at our option, replaced with a new product of equal or superior value if delivered to A.T.U.S. or an Authorized Service Center, prepaid, together with the sales slip or other proof of purchase date. **Prior approval from A.T.U.S. is required for return.** This warranty excludes defects due to normal wear, abuse, shipping damage, or failure to use product in accordance with instructions. This warranty is void in the event of unauthorized repair or modification, or removal or defacing of the product labeling.

For return approval and shipping information, contact the Service Department, Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224.

Except to the extent precluded by applicable state law, **A.T.U.S. will have no liability for any consequential, incidental, or special damages; any warranty of merchantability or fitness for particular purpose expires when this warranty expires.**

This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

Outside the U.S.A., please contact your local dealer for warranty details.



Audio-Technica U.S., Inc., 1221 Commerce Drive, Stow, Ohio 44224
<http://acctech.ru/cat/kondensatorskie-mikrofony>
www.audio-technica.com
 P51459-EN ©2002 Audio-Technica U.S., Inc. Printed in U.S.A.